S.N. 10/044,873

In th Claims

1.   (currently amended) A swinging article carrier assembly for mounting to <u>a</u> <u>receiver assembly carried on</u> to a motor vehicle, comprising:

a mounting arm [for securing to] <u>having a nonpivoting connection with the</u> <u>receiver assembly carried on</u> the vehicle;

a swing arm pivotally secured to said mounting arm; and

a base pivotally secured to said swing arm.

2.   (original) The carrier assembly of claim 1 further including an article carrier held on said base.

3.   (original) The carrier assembly of claim 2, wherein said article carrier has a cargo compartment with a watertight access door.

4.   (original) The carrier assembly of claim 1, wherein said swing arm is pivotally connected to said mounting arm at a first end and pivotally connected to said base at a second end.

5.   (original) The carrier assembly of claim 4, wherein said pivoting connection between said mounting arm and said swing arm is by a clevis and a pivot pin.

2

S.N. 10/044,873

6.   (original) The carrier assembly of claim 5, wherein said pivoting connection between said swing arm and said base is by a cooperating socket and stub shaft.

7.   (original) The carrier assembly of claim 4, wherein said pivoting connection between said swing arm and said base is by a cooperating socket and stub shaft.

8.   (currently amended) The carrier assembly of claim 1, wherein said [mounting arm] nonpivoting connection includes at least one mounting lug for securing to [a receiver] the receiver assembly carried on the vehicle.

9.   (currently amended) The carrier assembly of claim 1, wherein said [mounting arm] nonpivoting connection includes a pair of mounting bars for securing to [a receiver] the receiver assembly carried on the vehicle.

10.   (original) The carrier assembly of claim 1, further including a first pin for securing said mounting arm and said swing arm in a transport position.

11.   (original) The carrier assembly of claim 10, further including a second pin for securing said base in a home position with respect to said swing arm.